

Technical Datasheet

Date: 13.10.23

Page 1 of 1

EN ISO 13485 certified		
Article - No:	11-462-6000	Revision: 9
Remarks	max. volume: 185 ml / working volume: 170 ml	single use only

Specification

Product	Screw cap container PP, 170 ml, Ø58X99,5 mm, cap pre-assembled, container transparent, cap green, grading 3 sided, every 10ml, sterile EO
Colour	container transparent, cap green
Graduation	grading 3 sided, every 10ml
Nominal Capacity	170 ml
Material Characteristics	container: polypropylene (PP)
	cap: high-density polyethylene (HDPE)
Temperature range	-40°C - 120°C
Product Characteristics	leak proof of not less than 95 KPa (0,95 bar, 14 psi)
	biologically inert
	physiologically harmless
	no heavy metals according to EC/94/62
Purity Grade	do not contain any pyrogens
Sterilisation Process	gas sterilisation by ethyleneoxid, 10-6
Shelf - Life	36 months at controlled storage conditions
Packaging	pcs per bag: 110
	pcs per carton: 110
	pcs per pallet: 3.520
Storage	dry condition: 40%-60% rel. humidity
	bags / cases orig. closed
	storage temp. +2°C to max. +30°C
	pal. not stackable
Approved by nerbe plus quality department	